

EZCast Beam projector



| Products | EZCast Beam J2 | EZCast Beam V2 | EZCast Beam V3 |
|------------------------------|---|--|--|
| Projection technology | DLP | LCD | LCD |
| Brightness | 300 ANSI lumens | 200 ANSI lumens | 200 ANSI lumens |
| Contrast | 5000 : 1 | 1000 : 1 | 1000 : 1 |
| Output resolution | 854 x 480 | 1280 x 720 | 1280 x 720 |
| Input resolution | 1080p | 1080p | 1080p |
| Light source | LED | LED | LED |
| LED lumens | 10,000 lumens | 10,000 lumens | 10,600 lumens |
| LED life | >20,000 hours | >30,000 hours | >30,000 hours |
| Throw ratio | 1.3:1 | 1.45:1 | 1.5 : 1 |
| Focus | Manual | Manual | Manual |
| Throw distance | 0.86-2.88 M | 1-5.2 M | 1-5.2 M |
| Screen size | 30-100 inches | 32-176 inches | 32-176 inches |
| Aspect ratio | 16:9 | 16:9 | 16:9 |
| Wi-Fi | 2.4G | Wi-Fi adapter 2.4G / 5G | Wi-Fi adapter 2.4G / 5G |
| Bluetooth | N/A | N/A | V4.1+HS |
| Keystone | Auto vertical keystone and manual 2D keystone | Manual vertical correction | 2D electrical correction |
| Power | Input: 100-240V 50 / 60Hz Output: 15V / 2A | Input: 100-240V 50 / 60Hz Output: 19V / 3.42A | Input: 100-240V 50 / 60Hz Output: 19V / 3.42A |
| Battery | 9,000 mAh @ 3.7V | N/A | N/A |
| Input interface | USB / HDMI | USB*2 / HDMI / SD | USB*2 / HDMI / MicroSD |
| Output interface | 3.5 mm audio jack | 3.5 mm audio jack | 3.5 mm audio jack |
| Speaker | 4Ω 2W | 8Ω2W*2 | 4Ω5W*1 |
| Operating system | EZCast multimedia center | EZCast multimedia center | EZCast multimedia center |
| Language support | 22 Countries | 22 Countries | 22 Countries |
| Dimensions | 115 x 115 x 32 (mm) | 218 x 172 x 88 (mm) | 230 x 168.5 x 90 (mm) |
| Weight | 400g | 1,200g | 1,200g |